AMENDMENTS TO THE CLAIMS

This listing of the claims replaces all prior versions, and listing of the claims, in this application.

Listing of the Claims

- 1. (Canceled)
- 2. (Previously Presented) A control system, comprising:
 - a plurality of field devices,

at least one of the field devices providing a second control function within the control system, the second control function including controlling one or more devices,

a computing device providing a first control function within the control system, the first control function including controlling at least the field device that provides the second control function,

the computing device including a control subsystem comprising:

a bus,

a plurality of modules that are coupled to the bus and that each comprise a housing, and

at least a first module comprising a controller,

at least a second module interfacing one or more of the field devices,

at least a third module interfacing to the field device that provides the second control function.

- 3. (Previously Presented) A control system, comprising:
 - a computing device providing a first control function within the control system,
 - a plurality of field devices,
 - at least one of the field devices providing a second control function within the control system,
 - a control subsystem communicatively coupled to the computing device, the control subsystem comprising:
 - a bus,
 - a plurality of modules that are coupled to the bus and that each comprise a housing, and
 - at least a first module comprising a controller,
 - at least a second module interfacing one or more of the field devices,
 - at least a third module interfacing to the field device that provides the second control function

wherein the computing device downloads programs and data to the control subsystem.

- 4. (Currently Amended) A control system-according to claim 3, comprising A control system, comprising:
 - a computing device providing a first control function within the control system,
 - a plurality of field devices,
 - at least one of the field devices providing a second control function within the control system,

a control subsystem communicatively coupled to the computing device, the control subsystem comprising:

a bus,

a plurality of modules that are coupled to the bus and that each comprise a housing, and

at least a first module comprising a controller,

at least a second module interfacing one or more of the field devices,

at least a third module interfacing to the field device that provides the second control function

a support member that is adapted to mount to any of a wall and a DIN rail, at least one module being mechanically coupled to the support member-,

wherein the computing device downloads programs and data to the control subsystem.

- 5. (Previously Presented) A control system according to claim 3, wherein at least one of the field devices comprises a sensor.
- 6. (Previously Presented) A control system according to claim 3, wherein the bus is a multidrop bus.
- 7. (Currently Amended) A control system, comprising

a network,

a first control device that is coupled to the network,

a second control device that is coupled to <u>the</u> network for communication with at least the first control device,

one or more field devices,

at least one of the field devices comprising a third control device,

the second control device comprising

a bus,

a control processor that is coupled to the bus,

one or more modules that are coupled to the bus for communication with at least the control processor,

at least one of the modules comprising a housing, and

at least one of the modules being <u>adapted</u> adapted to serve as an interface to at least one field device,

at least one of the modules serving as an interface to, and controlling, the field device that comprises the third control device,

the first control device being configured to control the second control device.

8. (Currently Amended) A control system according to claim 7, comprising A control system, comprising

a network,

a first control device that is coupled to the network,

a second control device that is coupled to the network for communication with at least the first control device,

one or more field devices,

at least one of the field devices comprising a third control device,

the second control device comprising

<u>a bus,</u>

a control processor that is coupled to the bus,

one or more modules that are coupled to the bus for communication with at least the control processor,

at least one of the modules comprising a housing, and

at least one of the modules being adapted to serve as an interface to at least one field device,

at least one of the modules serving as an interface to, and controlling, the field device that comprises the third control device,

a support member that is adapted to mount to any of a wall and a DIN rail, at least one of the modules being mechanically coupled to the support member.

the first control device being configured to control the second control device.

- 9. (Previously Presented) A control system according to claim 7, wherein at least one of the field devices comprises a sensor.
- 10. (Previously Presented) A control system according to claim 7, wherein the bus is a multidrop bus.
- 11. (Currently Amended) A control system, comprising

a first control device and a second control device,

the first control device comprising

a bus,

a plurality of modules that are coupled to the bus,

a first module comprising a control processor,

at least one of the modules comprising a control processor,

at least one of the modules other than the first module adapted to provide an interface to a field device,

at least one other of the modules adapted to provide an interface to a field device,

at least one of the modules other than the first module serving as an interface to a field device that comprises the second control device,

at least one of the other modules serving as an interface to a field device that comprises the second control device,

at least one of the modules comprising a housing,

a computing device that is coupled to the first control device via a network, the computing device being configured to download programs to the first control device.

12. (Currently Amended) A control system according to claim 11, wherein A control system, comprising

a first control device and a second control device,

the first control device comprising

a bus,

a plurality of modules that are coupled to the bus,

at least one of the modules comprising a control processor,

at least one other of the modules adapted to provide an interface to a field device,

at least one of the other modules serving as an interface to a field device that comprises the second control device,

at least one of the other modules <u>including</u> includes interface logic that comprises a PCMCIA card-,

a computing device that is coupled to the first control device via a network, the computing device being configured to download programs to the first control device.

13. (Previously Presented) According to claim 12, wherein the interface logic further comprises

an interface controller in communication with the PCMCIA card, and

an external connector in communication with the PCMCIA card.

- 14. (Previously Presented) A control system according to claim 11, wherein the second control device executes programming for process control.
- 15. (Currently Amended) A control system according to claim 11, wherein A control system, comprising

a first control device and a second control device,

the first control device comprising

a bus,

a plurality of modules that are coupled to the bus,

at least one of the modules comprising a control processor,

at least one other of the modules adapted to provide an interface to a field device,

at least one of the other modules serving as an interface to a field device that comprises the second control device,

at least one of the other modules <u>comprising</u> comprises a PCMCIA card that is adapted for communications with the respective field device of that module.

a computing device that is coupled to the first control device via a network, the computing device being configured to download programs to the first control device.

16. (Currently Amended) A control system, comprising

a first control device that is coupled to a workstation via a network, the first control device comprising

a bus,

a plurality of modules that are coupled to the bus,

a first module comprising a control processor,

at least one of the modules comprising a control processor,

at least one of the modules other than the first module adapted to provide an interface to a field device,

at least one other of the modules adapted to provide an interface to a field device.

at least one of the modules other than the first module serving as an interface to a field device that comprises the second control device.

at least one of the other modules serving as an interface to a field device that comprises the second control device,

at least one of the modules comprising a housing,

the workstation being configured to download programs to the first control device.

17. (Currently Amended) A control system according to claim 16, wherein A control system, comprising

a first control device that is coupled to a workstation via a network, the first control device comprising

a bus,

a plurality of modules that are coupled to the bus,

at least one of the modules comprising a control processor,

at least one other of the modules adapted to provide an interface to a field device,

at least one of the other modules serving as an interface to a field device that comprises the second control device,

at least one of the other modules <u>comprising</u> comprises interface logic that includes a PCMCIA card-,

the workstation being configured to download programs to the first control device.

18. (Previously Presented) According to claim 17, wherein the interface logic further comprises

an interface controller in communication with the PCMCIA card, and an external connector in communication with the PCMCIA card.

19. (Currently Amended) A control system according to claim 16, comprising A control system, comprising

a first control device that is coupled to a workstation via a network, the first control device comprising

a bus,

a plurality of modules that are coupled to the bus,

at least one of the modules comprising a control processor,

at least one other of the modules adapted to provide an interface to a field device,

at least one of the other modules serving as an interface to a field device that comprises the second control device,

a support member that is adapted to mount to any of a wall and a DIN rail, wherein at least one of the modules is being mechanically coupled to the support member.

the workstation being configured to download programs to the first control device.

20. (Currently Amended) A control system according to claim 16, wherein A control system, comprising

a first control device that is coupled to a workstation via a network, the first control device comprising

a bus,

a plurality of modules that are coupled to the bus,

at least one of the modules comprising a control processor,

at least one other of the modules adapted to provide an interface to a field device,

at least one of the other modules serving as an interface to a field device that comprises the second control device,

at least one of the other modules <u>comprising</u> comprises a PCMCIA card that is adapted to serve as the interface to the respective field device of that module.

the workstation being configured to download programs to the first control device.

21. (Currently Amended) A control system, comprising

a computing device coupled to a network,

a first control device that is coupled to the computing device via the network, the first control device comprising

a bus,

a control processor that is coupled to the bus,

a plurality of modules that are coupled to the bus and that are adapted to serve as interfaces to field devices,

at least one of the modules comprising a housing,

at least one of the modules serving as an interface to, and controlling, a device that includes a second control device,

Atty. Docket No. 102314-157

Application No. 10/722,341 Examiner: Raymond Phan

wherein the computing device is configured to download programs to the first control device.

- 22. (Currently Amended) A control system according to claim 21, wherein at least one of the other modules other than the module interfacing the device that includes the second control device comprises interface logic.
- 23. (Currently Amended) A control system according to claim 22, wherein A control system, comprising

a computing device coupled to a network,

a first control device that is coupled to the computing device via the network, the first control device comprising

a bus,

a control processor that is coupled to the bus,

a plurality of modules that are coupled to the bus and that are adapted to serve as interfaces to field devices,

at least one of the modules serving as an interface to, and controlling, a device that includes a second control device,

at least one of the other modules comprising interface logic that the interface logic-comprises a PCMCIA card-,

wherein the computing device is configured to download programs to the first control device.

24. (Previously Presented) According to claim 23, wherein the interface logic further comprises

an interface controller in communication with the PCMCIA card, and

an external connector in communication with the PCMCIA card.

25. (Currently Amended) A control system according to claim 21, wherein wherein A control system, comprising

a computing device coupled to a network,

a first control device that is coupled to the computing device via the network, the first control device comprising

a bus,

a control processor that is coupled to the bus,

a plurality of modules that are coupled to the bus and that are adapted to serve as interfaces to field devices,

at least one of the modules serving as an interface to, and controlling, a device that includes a second control device,

at least one of the other modules <u>comprising</u> comprises a support member that is adapted to mount to a DIN rail.

wherein the computing device is configured to download programs to the first control device.

26. (Currently Amended) A control system according to claim 21, wherein A control system, comprising

a computing device coupled to a network,

a first control device that is coupled to the computing device via the network, the first control device comprising

a bus,

a control processor that is coupled to the bus,

a plurality of modules that are coupled to the bus and that are adapted to serve as interfaces to field devices,

at least one of the modules serving as an interface to, and controlling, a device that includes a second control device,

at least one of the other modules <u>comprising</u> comprises a PCMCIA card that is adapted to serve as the interface to the respective field device of that module.

wherein the computing device is configured to download programs to the first control device.

27. (Currently Amended) A control system, comprising

a first control device coupled to a network,

a second control device that is coupled to the first control device via the network, the second control device including

a control processor,

a plurality of modules that are coupled to one another and to the control processor by a bus, the modules being adapted to serve as interfaces to field devices,

at least one of the modules comprising a housing,

Examiner: Raymond Phan

at least one of the modules being adapted to serve as an interface to a field device that comprises a third control device.

- 28. (Currently Amended) A control system according to claim 27, wherein at least one of the other modules other than the module interfacing to the field device that comprises the third control device comprises interface logic.
- 29. (Currently Amended) A control system according to claim 28, wherein A control system, comprising

a first control device coupled to a network,

a second control device that is coupled to the first control device via the network, the second control device including

a control processor,

a plurality of modules that are coupled to one another and to the control processor by a bus, the modules being adapted to serve as interfaces to field devices,

at least one of the modules being adapted to serve as an interface to a field device that comprises a third control device,

at least one of the other modules comprising interface logic that the interface logic comprises a PCMCIA card.

30. (Currently Amended) According to claim 29 28, wherein the interface logic further comprises

an interface controller in communication with the PCMCIA card, and

an external connector in communication with the PCMCIA card.

Atty. Docket No. 102314-157

Application No. 10/722,341 Examiner: Raymond Phan

31. (Currently Amended) A control system according to claim 27, comprising A control system, comprising

a first control device coupled to a network,

a second control device that is coupled to the first control device via the network, the second control device including

a control processor,

a plurality of modules that are coupled to one another and to the control processor by a bus, the modules being adapted to serve as interfaces to field devices,

at least one of the modules being adapted to serve as an interface to a field device that comprises a third control device,

a support member that is adapted to mount to any of a wall and a DIN rail, wherein at least one of the modules is coupled to the support.

- 32. (Previously Presented) A control system according to claim 31, wherein the support member is adapted to mount to a DIN rail.
- 33. (Previously Presented) A control system according to claim 27, wherein the second control device is adapted to control the third control device.
- 34. (Previously Presented) A control system according to claim 27, wherein the second control device can be expanded to include further modules.
- 35. (Currently Amended) A control system according to claim 27, wherein A control system, comprising

a first control device coupled to a network,

a second control device that is coupled to the first control device via the network, the second control device including

a control processor,

a plurality of modules that are coupled to one another and to the control processor by a bus, the modules being adapted to serve as interfaces to field devices,

at least one of the modules being adapted to serve as an interface to a field device that comprises a third control device,

at least one of the other modules <u>comprising</u> eomprises a PCMCIA card that is adapted to serve as the interface to the respective field device of that module.

- 36. (New) A control system according to claim 2, wherein the housing is a field mountable housing.
- 37. (New) A control system according to claim 3, wherein the housing is a field mountable housing.
- 38. (New) A control system according to claim 7, wherein the housing is a field mountable housing.
- 39. (New) A control system according to claim 11, wherein the housing is a field mountable housing.
- 40. (New) A control system according to claim 16, wherein the housing is a field mountable housing.
- 41. (New) A control system according to claim 21, wherein the housing is a field mountable housing.
- 42. (New) A control system according to claim 27, wherein the housing is a field mountable housing.